

KT-SOL PLUS Heavy Duty (RXSOL-20-3201-025)

MATERIAL SAFETY DATA SHEET • SALALAH CHEMICAL, OMAN

1. Product and Company Identification

www.rxmarine.com

Product Name	RXSOL-20-3201-025
Product Type	KT - SOL PLUS Heavy Duty 25 Ltr

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

Stock Point ::: Mumbai, Kandla, Mundra, Chennai, Ennore, Kolkata, Haldia, Visakhapatnam, Gangavram, Fujairah, Muscat

Phone	+91 22 27815541 / 42
Fax	+91 22 2781 1318 :::AOH :0091 9821214367
Email	care@rxmarine.com
Website	www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

SURFACTANT (ANIONIC & NON-IONIC) , LAB , Potassium hydroxide Strong alkaline cleaner Declaration according recommendation 89/542/EEG.. chelating agents, meta silicate and additives (biodegradable > 90%)

*See Section 16

3. Hazards Identification

www.rxmarine.com



Corrosive

Environmental Hazards	None
Human Health Hazards	Moderates
R 35:Causes skin burning effects	

4. First Aid Measures

www.rxmarine.com

Inhalatin	Harmful,. supply or remove to fresh air and seek medical advice attention.
Skin Contact	Rinse with running water and soap. Skin care. Remove contaminated clothes.
Eye Contact	Flush with running water for at least 15 minutes Immediately .
Ingestion	Vomiting is dangerous , seek medical attention.

5. Fire-fighting Measures

www.rxmarine.com

Non Combustible Product

Suitable	N.A. can use foam dry Co2 , water-spray.
Not suitable	Not applicable
Special	Not applicable
Protection of fire Fighter	Not applicable

Special protective equipment for fire-fighters: Wear protective equipment.

6. Accidental Release Measures

www.rxmarine.com

Environmental Precaution	Direct flow into drainage system, surface or ground water is prohibited.
Cleaning Method	Flush Spill Area with Water and remove with liquid-absorbing material like foam sand,sawdust etc..

7. Handling and Storage

www.rxmarine.com

Condition to Avoid	Non flammable but avoid direct heating
Materials to Avoid	Do not subject to Acidic / Oxidizing Agents
Handling	Keep Container Tightly Closed

Note: Eyewash facilities require at workplace. The product causes corrosion on skin and mucous membranes. Please note that in case of discharge of acidic or alkaline products into the sewerage system, the pH must be in the range of 6-10 since higher or lower pH values may damage the sewerage system or impair biological dosage treatment plants. So that for maintaining pH we have to add acidic / basic medium neutraliser. For example, if pH is less than 6, basic neutraliser is required, and if pH is more than 10, acidic nature neutraliser is required. For details of any guideline, please visit our technical website www.rxmarine.com

• Dilute in water (always use plastic jar and RXSOL should be added to water, never add water to RXSOL.)

8. Exposure controls and personal protection

www.rxmarine.com

Personal protection :

Respiratory System Protection	Approved respirator must be worn when spraying
Eye Protection	Wear eye protection (on possibility of contact)
Hand protection	Wear PVC chemical resistance protective glove



Gloves



Suit



Goggles



No_Smoking

9. Physical and chemical properties

www.rxmarine.com

Product Properties:

Appearance	Pale clear liquid
Density	In g/cm ³ at 20°C: Spec. gravity : 1.035
Compatibility	
Metal	No known effect
Rubber	No known effect
pH	Alkaline (12.7 - 13)
Flash point	Not Applicable
Solubility	100% soluble in water
Packaging	Size (in Litres)

10. Stability and reactivitywww.rxmarine.com

Hazardous Decomposition Products	Do not occur if stored and used as directed. n FIRE combustion CO, CO ₂ , NH ₃ , SOX etc hazardous gas produced
----------------------------------	---

NOTE : Avoid Contact With Acid

11. Toxicological informationwww.rxmarine.com**Comment** - Not applicable , Emulsifies in water**12. Ecological information**www.rxmarine.com

95 % added surfactants are biodegradable as per by international regulation .This material must be disposed with local national regulations.

13. Disposal considerationswww.rxmarine.com

As per guide line of local rules and regulation and before disposal and neutralization pl. refer 07 article.

14. Transport informationwww.rxmarine.com

Proper Shipping Name				
UN				
	Proper Shipping Name	Sodium hydroxide, solution		
	UNNo.	1824		
	Hazard Class	8	PackingGroup	II
Road/Rail(ADR/RID)				

	Proper Shipping Name	Sodium hydroxide, solution		
	ADR UN No.	1824		
	ADR Hazard Class	8	Tremcard	80S1824
Sea(IMDG)				
	Proper Shipping Name	Sodium hydroxide, solution		
	IMDG UN No.	1824		
	IMDG Hazard Class.	8	IMDG Pack Group.	II
	IMDG EmS	F-A, S-A	IMDG subrisk	N/A
	IMDG Labels	8	IMDG Flash point	N/A
Air(ICAO/IATA)				
	Proper Shipping Name	Sodium hydroxide, solution		
	ICAO Un No.	1824		
	ICAO Hazard Class	8	ICAO Packing Group.	II
	ICAO subrisk	N/A	ICAO Labels	8, CAO
	ICAO Flashpoint	N/A		
DOT/ CFR (US Department of Transportation)				
	DOT Proper Shipping Name	Sodium hydroxide, solution		
	Hazardous Material	Sodium hydroxide		
	Hazard Class	8	Identification Number	UN 1824
	Product RQ (lbs)	3640	DOT subrisk	N/A
	DOT Labels	8	DOTFlashpoint	N/A

15. Regulatory information

www.rxmarine.com

Classification and labelling according to Chemicals Hazard Information and Packaging Regulations (CHIP). Symbols of danger C
Corrosive

R phrases	R 35 : Causes severe burns
S-phrases	S2: Keep out of reach of children S26 :In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28 : After contact with skin, wash immediately with plenty of water. S37/39 : Wear suitable gloves and eye/face protection.

16. Other information

www.rxmarine.com

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our product from the point of view of safety requirements and is not intended to guarantee any particular properties

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.