

Fuel Oil Treat FOT (RXSOL-70-7001-025)

MATERIAL SAFETY DATA SHEET • SALALAH CHEMICAL, OMAN

1. Product and Company Identification

www.rxmarine.com

Product Name	:	RXSOL 70-7001-025
Product Type	:	FUEL OIL TREATMENT
Revised Date	:	5th Jan'24

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

Branch Stock Point : Kolkata, Mumbai, Chennai, Visakhapatnam, Kandla - Gandhidham, Fujairah, Kenya, Nairobi, Canada

Phone	:	+91 22 27815541 / 42
Fax	:	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	:	mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	Concentration	CAS Number	EC Number	R Phrases*	Symbols
Naphtha(petroleum) ,hydrosulfurizedheavy	60-100	64742-82-1	265-185-4	65, 66	Xn
Iron carboxylate	1-5	61788-81-6	N/A	65	Xn
Fuel, diesel	5-10	68334-30-5	269-822-7	40	Xn
N-Oleyl- 1,3diaminopropane	0-1	7173-62-8	230-528-9	22 34 50	C,N
Aminoethylpiperazine	0.05	140-31-8	205-411-0	21/22, 34,43, 52/53	C

3. Hazards Identification

www.rxmarine.com

Odour	Smells of hydrocarbon.
Appearance	Liquid, dark, brown, insoluble in water.
Contact with eyes	Causes redness and irritation.
Contact with skin	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis.

Inhalation	In cases of severe exposure, anaesthesia may develop, May cause chronic pneumonitis, May cause coughing.
Ingestion	Harmful: may cause lung damage if swallowed (R65).Limited evidence of carcinogenic effect (R40).

4. First Aid Measures

www.rxmarine.com

Contact with skin	Remove contaminated clothing immediately and drench affected skin with plenty of water. Contaminated clothing should be laundered before reuse. Seek medical attention if irritation persists.
Contact with eyes	If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes. Irrigate eyes thoroughly whilst lifting eyelid. When in doubt or symptoms persist, seek medical attention.
Ingestion	Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected, obtain immediate medical attention. If vomiting occurs, turn patient on side. Obtain immediate medical attention.
Inhalation	Remove patient to fresh air. Seek medical attention if ill effects occur.
General	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

5. Fire-fighting Measures

www.rxmarine.com

- Auto-ignition point 250 deg C at 760 mm Hg
- Flash point >62 deg C (CC)
- Carbon oxides may be formed
- In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide (S43)
- Do not use water jets
- Prevent run off water from entering drains if possible
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback

6. Accidental Release Measures

www.rxmarine.com

Personal Precautions	Wear protective clothing as per section 8.
Environmental Precautions	Do not allow to enter public sewers and watercourses.
Immediate Actions	Contain spillage by any means possible.
Clean Up Actions	Absorb spillage in inert material and shovel up. Ventilate the area and wash spill site after material pick-up is complete.
Special Precautions	Do not allow to enter public sewers and watercourses. Wear protective clothing as per section 8.

7. Handling and Storage

www.rxmarine.com

Handling	Avoid contact with skin and eyes (S24/25).Eyewash bottles should be available.Wear protective clothing as per section
Storage	Keep only in the original container in a cool, well ventilated place (S3/9/49).Keep container tightly closed (S7).Keep away from open flames, hot surfaces and sources of ignition.

8. Exposure controls and personal protection

www.rxmarine.com

Exposure Limits	TLV (TWA) 275 mg/m3 (Naphtha, low boiling, hydrogen treated)
Exposure controls	No special ventilation is required unless the product is used in a spray form
Occupational exposure controls	No respiratory protection is required unless subject to contact with substance mist.During fumigation/spraying wear suitable respiratory equipment (S42).Wear suitable protective clothing, including eye/face protection and gloves (neoprene or nitrile are recommended)

9. Physical and chemical properties

www.rxmarine.com

Odour	Smells of Hydrocarbon
Appearance	Liquid, dark, brown, insoluble in water
pH	Not applicable
Boiling point	170 °C to 210 °C at 760 mm /Hg
Vapour pressure	Not known
Vapour density	(air = 1) >1
Freezing point	unknown
Insoluble in water	
Specific gravity (water=1)	0.835
Flash point >	62 deg C (CC)
Auto-ignition point	250 deg C at 760 mm Hg
Lower explosive limit	0.5 % (in air)
Upper explosive limit	7 % (in air)

10. Stability and reactivity

www.rxmarine.com

- This article is considered stable under normal conditions
- Keep away from naked flames, incandescent or hot surfaces
- See Section 5

11. Toxicological information

www.rxmarine.com

Toxicological information	No experimental data available.
Inhalation	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Contact with skin	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis. Contains Aminoethylpiperazine. May produce an allergic reaction.
Contact with eyes	Causes irritation.
Ingestion	Aspiration hazard , Harmful: may cause lung damage if swallowed (R65).
Carcinogenicity	Limited evidence of carcinogenic effect (R40).

12. Ecological information

www.rxmarine.com

Ecotoxicity	May cause acute effects in the aquatic environment. This product contains components which are classified in the EU as dangerous for the environment.
Mobility	Insoluble in water
Persistence and Biodegradability	The components in this product are readily biodegradable.
Bioaccumulation Potential	Hydrocarbon solvents have the potential to bioaccumulate.
Other Adverse Effects	No environmental problems are expected when the product is used / handled correctly. In its intended use, the product will not be released into the environment.

13. Disposal considerations

www.rxmarine.com

Classification	EU Waste class: 07.01. This material and/or its container must be disposed of as hazardous waste
Disposal considerations	Do not discharge into drains or the environment, dispose to an authorised waste collection point. Disposal should be in accordance with local, state or national legislation

14. Transport information

www.rxmarine.com

Not classified as hazardous for transport.

15. Regulatory information

www.rxmarine.com

Classification and labelling	Contains Aminoethylpiperazine. May produce an allergic reaction.
Risk Phrases	Limited evidence of carcinogenic effect (R40). Harmful: may cause lung damage if swallowed (R65). Repeated exposure may cause skin dryness or cracking (R66). Contains Dimethylpiperazine. May produce an allergic reaction.
Safety Phrases	Wear suitable protective clothing, eye/face protection and gloves (S36/37/39). In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45). If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label (S62).

16. Other information

www.rxmarine.com

Text of R and S phrase codes used in this safety data sheet:- R21/22: Harmful in contact with skin and if swallowed; R22: Harmful if swallowed; R34: Causes burns; R40: Limited evidence of carcinogenic effect; R43: May cause sensitisation by skin contact; R50: Very toxic to aquatic organisms; R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment; R65: Harmful: may cause lung damage if swallowed; R66: Repeated exposure may cause skin dryness or cracking. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties. The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.