

Sodium Bisulphite Solution (RXSOL-19-1524-050)

MATERIAL SAFETY DATA SHEET • SALALAH CHEMICAL, OMAN

1. Product and Company Identification

www.rxmarine.com

Product Name	RXSOL-19-1524-050
Product Type	Sodium Bisulphite

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point ::: Mumbai, Kandla, Chennai, Visakhapatnam, Kolkata, Fujairah, Muscat

Phone	+91 22 27815541 / 42
Fax	+91 22 2781 1318+91 22 2781 1318 :::AOH :0091 9821214367
Email	mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

CAS #	Chemical Name	Percent
763-90-5	Sodium Bisulfite	40%

Toxicological Data on ingredients: sodium bisulfate : ORAL (LD50) : Acute : 200MG/KG (Rat)

Customize packing of Sodium Bisulfite solution also available with us. We have various ratio as per end user requirements SODIUM BISULPHITE 20% CONCENTRATION, 10% and 30%, 40% also available with us.

3. Hazards Identification

www.rxmarine.com

Eye Contact	Irritant
skin contact	Irritant
inhalation	It inhaled remove to fresh air,if not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person
Carcinogenic effect	na
MUTAGENIC EFFECTS:	Mutagenic for bacteria and / or yeast

4. First Aid Measures

www.rxmarine.com

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention.
Skin Contact	In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Serious Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air; if not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Serious Inhalation	Not available.
Ingestion	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie belt or waistband.
Serious Ingestion:	Not available.

5. Fire-fighting Measures

www.rxmarine.com

Flammability of the Product	Non-flammable
Auto-Ignition Temperature	Not applicable.
Flash Points	Not applicable.
Products of Combustion	Not available.
Fire Hazards in Presence of Various Substances	Not applicable.
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact : Not available. Risks of explosion of the product in presence of static discharge: Not available
Fire Fighting Media and Instructions	Not applicable.
Special Remarks on Explosion Hazards:	Not available.

6. Accidental Release Measures

www.rxmarine.com

Small Spill	Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.
Large Spill	Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

7. Handling and Storage

www.rxmarine.com

Precautions	Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes, keep away from incompatibles such as oxidizing agents, alkalis.
Storage	Keep container tightly closed. Keep Container in a cool, well-ventilated area.

8. Exposure controls and personal protection

www.rxmarine.com

Engineering Controls	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.
Personal Protection	Splash goggles. Lab coat, Dust respirator. Be sure to use an approved / certified respirator or equivalent Gloves.
Personal Protection in case of a Large Spill"	Splash goggles. Full suit. Dust respirator. Boots Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Exposure Limits	TWA 5 (mg/m³) from OSHA (PEL) [united states] Inhalation TWA 5 (mg/m³) from ACGIH (TLV) [united states] Inhalation TWA 5 (mg/m³) from [united states] Inhalation TWA 5 (mg/m³) from [United Kingdom(UK)] Inhalation TWA 5 (mg/m³) from [Canada] inhalation Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

www.rxmarine.com

Technical Specification :::

Formula	NaHSO ₃
Molecular Weight	104
Sodium Bisulfite, wt% (Na ₂ S ₂ O ₅)	38.0 - 42.0
Sodium Sulfate, wt%	≤ 3.5%
Solubility (10 % Aqueous Soln)	V. S. Hazy to clear solution.
pH Value of 5% Solution	3.5 to 4.5

Specific Gravity @ 25° C	1.310 - 1.370
Density, lbs/gal @ 25° C	10.9 - 11.3
Description	Sodium Bisulfite 40% Solution (NaHSO ₃) is a pale yellow liquid.
Standard Packing	50 Kg. / 250 kg HM HDPE Barrel

10. Stability and reactivity

www.rxmarine.com

Stability	The product is stable.
Instability Temperature	Not available.
Conditions of Instability	Incompatible materials
Incompatibility with various substances	Reactive with oxidizing agents, acids.
Corrosivity	Non - corrosive in presence of glass.
Special Remarks on Reactivity	Slowly oxidized to sulfate on exposure to air.
Special Remarks on Corrosivity	Not available.
Polymerization	Will not occur.

11. Toxicological information

www.rxmarine.com

Routes of Entry	Inhalation, Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 2000 mg/kg [Rat].
Chronic Effects on Humans	CARCINOGENIC EFFECTS :3 (Not classifiable for human.) by IARC. MUTAGENIC EFFECTS :Mutagenic for bacteria and/or yeast. May cause damage to the following organs: lungs, skin.
Other Toxic Effects on Humans	Hazardous in case of skin contact (irritant), of ingestion, of inhalation.
Special Remarks on Toxicity to Animals	Not available
Special Remarks on Chronic Effects on Humans	May affect genetic material (mutagenic). May cause cancer based on animal test data. No human data found.

Special Remarks on other Toxic Effects on Humans	Acute Potential Health Effects: Skin Causes skin irritation. Eyes. Causes eye irritation. Inhalation :Can cause respiratory tract irritation with cough, Wheezing, and Shortness of breath. It can produce anaphylaxis or other hypersensitivity reactions in some sensitized individuals. Ingestion :May be harmful if swallowed. It may cause nausea, vomiting ,diarrhea, abdominal pain, gastric. Extremely large amounts may affect behavior / central nervous system and may produce central nervous system stimulation,irritation,seizures and may also cause, cyanosis, respiratory depression, apnea,circulatory disturbances, hypotension and cardiovascular collapse.May cause asthmatic reaction in sensitized individuals. Chronic Potential Health Effects: Inhalation : Prolonged or repeated inhalation may cause bronchitis to develop with cough, phlegm, and/or shortness of breath. It can cause an asthma-like allergy or other hypersensitivity reactions such as anaphylaxis, angioedema, bronchoconstriction, flushing, diaphoresis, urticaria, tachycardia, and hypotension in sensitized individuals. Future exposures may cause shortness of breath. Wheezing, cough, and/or chest tightness. Skin:Prolonged or repeated skin contact can cause dermatitis. Ingestion : Prolonged or repeated ingestion may affect the liver, and blood
--	--

12. Ecological information

www.rxmarine.com

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.
Toxicity of the Products of Biodegradation	The products of degradation are less toxic than the product itself.
Special Remarks on the Products of Biodegradation	Not available.

13. Disposal considerations

www.rxmarine.com

Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
----------------	--

14. Transport information

www.rxmarine.com

DOT Classification	Not a DOT controlled material (United States).
Identification	Not applicable.
Special Provisions for Transport	Not applicable.

15. Regulatory information

www.rxmarine.com

Federal and state Regulations:

Connecticut hazardous material survey : Sodium bisulfite

Illinois toxic substances disclosure to employee act: Sodium bisulfite

Illinois chemical safety act: Sodium bisulfite

New York release reporting list: Sodium bisulfite

Pennsylvania RTK : Sodium bisulfite

Minnesota :Sodium bisulfite

Massachusetts RTK : Sodium bisulfite

Massachusetts spill list : Sodium bisulfite

New Jersey : Sodium bisulfite

New Jersey spill list : Sodium bisulfite

Louisiana spill reporting : Sodium bisulfite

California Director's List of Hazardous Substances: Sodium bisulfite

TSCA 8(b) inventory Sodium bisulfite

TSCA 8(a) PAIR : Sodium bisulfite

TSCA 8(d) H and S data reporting : Sodium bisulfite: Effective date :1/26/94; Sunset date : 6/30/98

CERCLA : Hazardous substances : Sodium bisulfite : 5000 lbs. (2268 kg)

Other Regulations:

OSHA Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

EINECS : This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): CLASS D-2B: Material causing other toxic effects (TOXIC)

DSCL (EEC):

R22- Harmful if swallowed.

R31- Contact with acids liberates toxic gas.

S25- Avoid contact with eyes.

S46- If swallowed, seek medical advice immediately and show this container or label.

HMIS (U.S.A.):

Health Hazard :2

Fire Hazard :0

Reactivity :0

Personal Protection :E

National Fire Protection Association (U.S.A.):

Health :2

Flammability :0

Reactivity :0

Specific hazard :

Protective Equipment:

Gloves

Lab coat

Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.

Splash goggles.

16. Other information

www.rxmarine.com

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall rxmarine.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if RXMARINE has been advised of the possibility of such damages.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.