

HydroxylAmmonium Chloride (RXSOL-19-3212-050)

MATERIAL SAFETY DATA SHEET • SALALAH CHEMICAL, OMAN

1. Product and Company Identification

www.rxmarine.com

Product Name	Hydroxylammonium chloride
Part Number	RXSOL-19-3212-050

Company Details:....

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone	+91 22 20871200 - 1400
Fax	+91 22 27612100 ::AOH :0091 9821214367
Email	mail@rxmarine.com
Website	www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Substances

Synonyms	Hydroxylammonium chloride
Formula	H2NOH.HCl
Molecular weight	69,49 g/mol
CAS-No.	5470-11-1
EC-No.	226-798-2
Index-No.	612-123-00-2

Component	Classification	Concentration
Hydroxylammonium chloride		
CAS-No. 5470-11-1 EC-No 226-798-2 Index-No. 612-123-00-2	Met. Corr. 1; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2; Skin Sens. 1; Carc. 2; STOT RE 2; Aquatic Acute 1; Aquatic Chronic 2; H290, H302, H312, H315, H319, H317, H351, H373, H400, H411 M-Factor - Aquatic Acute:1	= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

3. Hazards Identification

www.rxmarine.com

Classification of the substance or mixture

Corrosive to Metals, (Category 1)	H290: May be corrosive to metals
Acute toxicity, (Category 4)	H302: Harmful if swallowed.
Acute toxicity, (Category 4)	H312: Harmful in contact with skin.
Skin irritation, (Category 2)	H315: Causes skin irritation.
Eye irritation, (Category 2)	H319: Causes serious eye irritation.
Skin sensitization, (Category 1)	H317: May cause an allergic skin reaction.
Carcinogenicity, (Category 2)	H351: Suspected of causing cancer.
Specific target organ toxicity - repeated exposure, (Category 2), spleen	H373: May cause damage to organs through prolonged or repeated exposure if swallowed.
Short-term (acute) aquatic hazard, (Category 1)	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, (Category 2)	H411: Toxic to aquatic life with long lasting effects.

Label elements

Signal Word	Warning
Hazard Statements	H290 May be corrosive to metals. H302 + H312 Harmful if swallowed or in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H351 Suspected of causing cancer. H373 May cause damage to organs (spleen) through prolonged or repeated exposure if swallowed. H410 Very toxic to aquatic life with long lasting effects.
Precautionary Statements	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301 + P312 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. P302 + P352 + P312 IF ON SKIN: Wash with plenty of water.Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention.
Supplemental Hazard Statements	None
Reduced Labeling (= 125 ml)	
Signal Word	Warning
Hazard statement(s)	H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.
Precautionary statement(s)	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Supplemental Hazard Statements	None
Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

4. First Aid Measures

www.rxmarine.com

Description of first aid measures

General advice	Show this material safety data sheet to the doctor in attendance.
If inhaled	After inhalation: fresh air. Call in physician.
In case of skin contact	In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.
In case of eye contact	After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.
If swallowed	After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.
Most important symptoms and effects, both acute and delayed	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

5. Fire-fighting Measures

www.rxmarine.com

Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture	Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Nitrogen oxides (NO_x) Hydrogen chloride gas Ambient fire may liberate hazardous vapours. Container explosion may occur under fire conditions. Not combustible. Risk of dust explosion. In the event of decomposition: danger of explosion! Avoid shock and friction.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Further information	May explode when heated. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system. spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Environmental precautions	Do not let product enter drains.
Methods and materials for containment and cleaning up	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.
Reference to other sections	For disposal see section 13.

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling

Advice on safe handling	Work under hood. Do not inhale substance/mixture.
Hygiene measures	Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.
Conditions for safe storage, including any incompatibilities	
Storage conditions	No metal containers. Tightly closed and away from sources of ignition and heat. Observe national regulations. Air and moisture sensitive.
Storage class	Storage class (TRGS 510): 4.1A: Other explosive hazardous materials
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. Exposure controls and personal protection

www.rxmarine.com

Control parameters

Ingredients with workplace control parameters

Exposure controls

Personal protective equipment

Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles
Skin protection	This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Chloroprene Minimum layer thickness: 0,65 mm Break through time: 480 min Material tested:KCL 720 Camapren® This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Latex gloves Minimum layer thickness: 0,6 mm Break through time: 60 min Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M).
Body Protection	Protective clothing

Respiratory protection	Required when dusts are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system. Recommended Filter type: Filter type P3 The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Control of environmental exposure	Do not let product enter drains.

9. Physical and chemical properties

www.rxmarine.com

Physical state	Crystalline powder Chunks
Colour	White
Odor	Slight chlorine
Melting point/freezing point	Melting point/ range: 155 - 157 °C - dec.
Initial boiling point and boiling range	No data available
Flammability (solid, gas)	The product is not flammable. - Flammability (solids)
Upper/lower flammability or explosive limits	No data available
Flash point	Not applicable
Autoignition temperature	No data available
Decomposition temperature	> 150 °C Heating may cause an explosion.
pH	2,5 - 3,5 at 50 g/l at 20 °C
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
Water solubility	ca.470 g/l at 20 °C - OECD Test Guideline 105
Partition coefficient: n-octanol/water	- Not applicable for inorganic substances
Vapor pressure	0,001 hPa at 50 °C - OECD Test Guideline 104
Density	1,67 g/cm ³ at 25 °C - lit.
Relative density	No data available
Relative vapor density	No data available
Particle characteristics	No data available
Explosive properties	No data available
Oxidizing properties	None
Other safety information	
Surface tension	ca.71,8 m N/m at 1,025g/l at 20 °C

10. Stability and reactivity

www.rxmarine.com

Reactivity	Sensitive to shock Risk of dust explosion.
Chemical stability	The product is chemically stable under standard ambient conditions (room temperature)
Possibility of hazardous reactions	Violent reactions possible with: Alkaline substances Possible formation of: Hydroxylamine Risk of explosion with: Fire-promoting substances Oxidizing agents
Conditions to avoid	Air Exposure to moisture. May be unstable at temperatures above: 75° C Heating (decomposition). No information available
Incompatible materials	No data available
Hazardous decomposition products	In the event of fire: see section 5

11. Toxicological information

www.rxmarine.com

Information on toxicological effects

Acute toxicity	LD50 Oral - Rat - male and female - 642 mg/kg (OECD Test Guideline 401) Acute toxicity estimate Oral - 642 mg/kg (ATE value derived from LD50/LC50 value) Inhalation: No data available Acute toxicity estimate Dermal - 1.100,1 mg/kg (Expert judgment) Remarks: (Regulation (EC) No 1272/2008, Annex VI)
Skin corrosion/irritation	Skin - In vitro study Result: Irritating to skin. - 42 min (OECD Test Guideline 439)
Serious eye damage/eye irritation	Eyes - In vitro study Result: Eye irritation - 6 h Remarks: (ECHA)
Respiratory or skin sensitization	Maximization Test - Guinea pig Result: positive (OECD Test Guideline 406)

Germ cell mutagenicity	Test Type: Ames test Test system: S. typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: with and without metabolic activation Result: negative Remarks: (ECHA) Test Type: Rat Test system: Embryo Remarks: Morphological transformation. Test Type: Hamster Test system: Lungs Remarks: Sister chromatid exchange Test Type: Mutagenicity (mammal cell test): micronucleus. Species: Mouse Cell type: Red blood cells (erythrocytes) Application Route: Oral Method: OECD Test Guideline 474 Result: negative
Carcinogenicity	Suspected of causing cancer.
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Specific target organ toxicity - repeated exposure	Ingestion - May cause damage to organs through prolonged or repeated exposure. - spleen Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Aspiration hazard	No data available
Additional Information	
Endocrine disrupting properties Product	
Assessment	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. RTECS: NC3675000 To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12. Ecological information

www.rxmarine.com

Toxicity	
Toxicity to fish	Semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - 1,78 mg/l - 96 h (OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates	Semi-static test EC50 - Daphnia magna (Water flea) - 1,1 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	Static test ErC50 - Pseudokirchneriella subcapitata - 0,21 mg/l - 72 h (OECD Test Guideline 201) Static test EC10 - Raphidocelis subcapitata (freshwater green alga) - 0,075 mg/l - 72 h (OECD Test Guideline 201)
Persistence and degradability	The methods for determining biodegradability are not applicable to inorganic substances.
Bioaccumulative potential	No data available
Mobility in soil	No data available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	
Assessment	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other adverse effects	No data available .

13. Disposal considerations

www.rxmarine.com

Waste treatment Method	No data available
------------------------	-------------------

14. Transport information

www.rxmarine.com

UN number	ADR/RID:3260 IMDG:3260 IATA: 3260
UN proper shipping name	ADR/RID: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (Hydroxylammonium chloride) IMDG: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (Hydroxylammonium chloride) IATA: Corrosive solid, acidic, inorganic, n.o.s. (Hydroxylammonium chloride)
Transport hazard class(es)	ADR/RID: 8 IMDG: 8 IATA:8
Packaging group	ADR/RID: III IMDG: III IATA:III
Environmental hazards	ADR/RID: no IMDG Marine pollutant: no IATA: no
Special precautions for user	
Tunnel restriction code	(E)
Further information	No data available

15. Regulatory information

www.rxmarine.com

Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
Authorisations and/or restrictions on use	

National legislation Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	E1 ENVIRONMENTAL HAZARDS
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.
Chemical Safety Assessment	For this product a chemical safety assessment was not carried out

16. Other information

www.rxmarine.com

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
-------------------	---