

Alum Liquid 30 (RXSOL-40-1171-025)

MATERIAL SAFETY DATA SHEET • SALALAH CHEMICAL, OMAN

1. Product and Company Identification

www.rxmarine.com

Product Name	Aluminium Sulphate Solution (Alum 30 percent)
Synonyms	Liquid Alum, Aluminium Sulphate 30 percent, Alum Solution

Alum is used as a coagulating agent in municipal and industrial water and wastewater treatment and as an additive in papermaking.

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

Stock Point ::: Mumbai, Fujairah, Muscat, Kandla, Chennai, Visakhapatnam, Kolkata

Phone	+91 22 27815541 / 42
Fax	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	123@rxmarine.com
Website	www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	CAS Number	EC Number	Composition
Aluminum Sulfate	10043-01-3	233-135-0	30% w/w (solution basis)
Non-Hazardous Mixture	7732-18-5	231-791-2	70% w/w (solution basis)

3. Hazards Identification

www.rxmarine.com

Classification (GHS/CLP)	Category	Hazard Statements
Corrosive to metals	Category 1	H290: May be corrosive to metals
Skin corrosion/irritation	Category 2	H315: Causes skin irritation
Serious eye damage/irritation	Category 1	H318: Causes serious eye damage
STOT (single exposure - respiratory tract)	Category 3	H335: May cause respiratory irritation

4. First Aid Measures

www.rxmarine.com

Exposure Route	First Aid Instructions
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Seek medical attention immediately.
Skin Contact	Immediately remove contaminated clothing. Wash skin thoroughly with plenty of water and soap. Seek medical advice if irritation persists. Wash contaminated clothing before reuse.

Exposure Route	First Aid Instructions
Eye Contact	Rinse cautiously with plenty of water for at least 15 minutes, holding eyelids open. Remove contact lenses if present and easy to do, then continue rinsing. Seek immediate medical attention (risk of serious eye damage).
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Give small amounts of water if conscious. Never give anything by mouth to an unconscious person. Seek medical attention immediately.

Most Important Symptom/Effect

Severe eye irritation or burns, possible permanent eye damage.

Skin irritation, redness, or burns on prolonged exposure.

Respiratory tract irritation if mist or vapors are inhaled

5. Fire-fighting Measures

www.rxmarine.com

-Non combustible.

-Product will not ignite, but may burn. Caution: Sufficient heat may produce toxic gases. Product will decompose at its melting point [770°C (1418°F)]. In contact with water and metals, flammable hydrogen gas can be generated which can result in a fire hazard. Sealed containers can rupture violently in the heat of a fire-Not flammable. In case of fire use extinguishing media appropriate to surrounding conditions.

-When heated above 650-770°C (1200-1418°F) Aluminum Sulfate forms sulfur dioxide, sulfur trioxide, aluminum oxide and sulfuric acid.

Extinguishing Media : Dry chemical, foam, carbon dioxide. Do not use water; corrosive sulfuric acid will form.

NFPA Ratings: Health: 2 Fire: 0 Instability: 1 Other:

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

6. Accidental Release Measures

www.rxmarine.com

Containment Procedures: Stop the flow of material, if this can be done without risk. Contain the discharged material. If sweeping of a contaminated area is necessary use a dust suppressant agent, which does not react with product (see Section 10 for incompatibility information).

Clean-Up Procedures: Wear appropriate protective equipment and clothing during clean -up. Shovel the material into waste container. Thoroughly wash the area after a spill or leak clean-up. Solutions of the compound can be neutralized with lime or similar compound. Avoid contamination of soil, and prevent spill residue from running to groundwater or storm drains.

Evacuation Procedures: Evacuate the area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Keep materials that burn away from spilled material. In case of large spills, follow all facility emergency response procedures.

Special Procedures : Remove soiled clothing and launder before reuse. Avoid all skin contact with the spilled material. Have emergency equipment readily available

7. Handling and Storage

www.rxmarine.com

Handling : All employees who handle this material should be trained to handle it safely. Do not breathe dust. Avoid all contact with skin and eyes. Use this product only with adequate ventilation. Wash thoroughly after handling.

Storage Procedures : Keep container tightly closed when not in use. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be store in secondary containers or in a diked area, as appropriate. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Use corrosion-resistant structural materials, lighting, and ventilation system in the storage area. Floors should be sealed to prevent absorption of this material. Have appropriate extinguishing equipment in the storage area (i.e., sprinkler system, portable fire extinguishers). Empty containers may contain residual particulates; therefore, empty containers should be handled with care. Do not cut, grind, weld or drill near this container. Never store food, feed, or drinking water in container that held this product. Keep this mateial away from food, drink and animal feed. Inspect all incoming containers before storage, to ensure container are properly labeled and not damaged. Do not store this material in open or unlabeled containers. limit quantity of material stored. Store in suitable containers that are corrosion-resitnt. Keep containers closed-material is hygroscopic.

8. Exposure controls and personal protection

www.rxmarine.com

PERSONAL PROTECTIVE EQUIPMENT

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (begining at 1910.132). Please reference applicable regulations and standards for relevant details.

Eyes/Face : Wear chemical safety goggles. If necessary, refer to U.S. OSHA 29 CFR 1910.133.

Skin: Where contact is likely, wear chemical resistant gloves, rubber boots, and coveralls. Buty rubber, natural rubber, polyethylene, polyvinyl chloride or neoprene gloves are recommanded. Gloves should be tested to determine suitability for prolonged contact with this material.

Respiratory : None required where adequate ventilation condition exist. If airborne concentrations are above the applicable exposure limits, use approved respiratory protection. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmosphere, use of a full-facepiece pressure/demand SCBA or full facepiece.

General : Wash hands thoroughly after handling material. Do not eat, drink or smoke in work areas. Have a safety shower or eye-wash fountain available. Use good hygiene practices when handling this material including changing and laundering work clothing after use. Discard contaminated shoes and leather goods.



Gloves



Suit

9. Physical and chemical properties

www.rxmarine.com

Appearance	:Lustrous white to grayish-white
Odor	:Odorless
Physical State	:Powder
pH	:3.0-4.0 (5% aqueous solution at 25 deg C)
Vapor Pressure	:Essentially 0 mm Hg
Vapor Density	: Not applicable
Boiling Point	: > 1600 deg C (2912 deg F)
Freezing/Melting Point	: Decomp at 770 deg C (1418 deg F)

Solubility in Water	: 87.5 g/100mL at 20 deg C
Softening Point	: Not applicable
Evaporation Rate	: Not applicable
Viscosity	: Not applicable
Bulk Density	: 0.96 g/cc
Percent Volatile	: Not available
Chemical Formula	: Al ₂ (SO ₄) ₃ •17 H ₂ O

The data provided in this section are to be used for product safety handling purposes. Please refer to Product Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

10. Stability and reactivity

www.rxmarine.com

Stability: Normally stable. When exposed to air, loss of combined water molecules by a hydrated material, such as this compound, will result in partial decomposition. Aluminum Sulfate is hygroscopic and will absorb moisture from the air. Avoid contact with moisture, excessive heat and incompatible materials listed below.

Incompatibility : Aluminum Sulfate is incompatible with strong oxidizing agents and strong bases (may react violently), moisture and most common metals in presence of moisture.

Hazardous Decomposition : Thermal decomposition: Sulfur dioxide, sulfur trioxide, and aluminum oxide. In contact with water: sulfuric acid.

Hazardous Polymerization : Will not occur.

11. Toxicological information

www.rxmarine.com

Acute Toxicity : Severely irritating or corrosive to the skin, eyes and gastrointestinal tract. Prolonged exposure to the skin may cause numbing effects. Product can cause severe irritation and inflammation of the eyes. Concentrated solutions may cause permanent damage to eyes .

LD50 (Unreported-Rat) 410 mg/kg; LD50 (Oral-Mouse) 6207 mg/kg; LD50 (Intraperitoneal-Mouse) 274 mg/kg; LD50 (Unreported-Mouse) 520 mg/kg; LD50 (Unreported-Guinea Pig) 490 mg/kg

Carcinogenicity : Information not available.

Carcinogenicity : This compound is not listed by ACGIH, EPA, IARC, OSHA, NIOSH, or NTP.

Neurotoxicity : With extensive exposures, aluminum may accumulate in brain tissue producing neurotoxicity, including encephalopathy and seizures (based on animal data).

Mutagenicity : A solution of Aluminum Sulfate in water produced positive results in cultured human cells (leukocytes), via sister chromatid exchanges, micronuclei and chromosomal aberrations). Negative results have been obtained in bacteria and cultured

mammalian cells.

Other Toxicological Information : On occasion workers chronically exposed to aluminum-containing dusts or fumes have developed severe pulmonary reactions including fibrosis, emphysema and pneumothorax. A much rarer encephalopathy has also been described. The factors which predispose to lung damage are not well characterized.

12. Ecological information

www.rxmarine.com

Ecotoxicity : Spills into water will result in hydrolysis to sulfuric acid solution with the capability of producing burns. TLm (mosquito fish) 48 hours = 240 ppm; Fatal (fundulus) 36 hours = 14 ppm (fresh water); LC50 (Largemouth bass) 96 hours = 250 ppm

Environmental Fate

Bioconcentration: No potential for food chain concentration. Aluminum sulfate will slowly be precipitated to $\text{Al}(\text{OH})_3$ due to natural alkalinity. A study was undertaken to assess the possibility of aluminum bioaccumulation (in rainbow trout). Trout tissues, plankton, and water were analyzed for total aluminum concentration. Statistical comparisons of experimental and control tissues revealed few overall significant differences in the level of aluminum between alum-exposed and non-exposed fish, but significant differences existed between tissues within a given treatment and age class

13. Disposal considerations

www.rxmarine.com

As shipped, product is not considered a hazardous waste by the EPA. However, product should be tested for corrosivity to determine if Waste Number D002 applies. No EPA Waste Numbers are applicable for this compound.

Disposal Instructions : Review federal, provincial, and local government requirements prior to disposal. Disposal by controlled incineration or secure landfill may be acceptable.

14. Transport information

www.rxmarine.com

NOTE:

Shipping Name: Non-regulated

Hazard Class: Not Applicable

Packing Group: Not Applicable Required Label(s): None

Name: Environmentally hazardous substance, solid, n.o.s. (aluminum sulfate)

Passenger & Cargo Aircraft Packing Instruction: 911 **Passenger & Cargo Aircraft Maximum Net Quantity:** 400 kg

International Maritime Organization (I.M.O.) Classification : Aluminum Sulfate is not regulated under I.M.O.

- Not classified as hazardous for transport

15. Regulatory information

www.rxmarine.com

RISK PHRASES : R-41 Risk of serious damage to eyes.

SAFETY PHRASES: S-39 Wear eye/face protection.

S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

UK REGULATORY REFERENCES: The Control of Substances Hazardous to Health Regulations 1988. Chemicals (Hazard Information & Packaging) Regulations 1993. Classification, Packaging and Labelling Regulations 1984.

COMMENTS: This material does not require classification, however in view of its potential to cause ocular damage it has been classified as Xi in accordance with suppliers data/information.

16. Other information

www.rxmarine.com

RX Marine International shall not be responsible for the use of any information, product, method, or apparatus herein presented ("Information"), and you must make your own determination as to its suitability and completeness for your own use, for the protection of the environment, and for health and safety purposes. You assume the entire risk of relying on this Information. In no event shall RX Marine International be responsible for damages of any nature whatsoever resulting from the use of this product or products, or reliance upon this Information. By providing this Information, RX Marine International neither can nor intends to control the method or manner by which you use, handle, store, or transport. This information could include technical inaccuracies or typographical errors. RX Marine International may make improvements and/or changes in the product (s) and/or the program (s) described in this information at any time. Customers should always satisfy themselves, that the product which they have selected is entirely suitable for their purpose under their conditions of use and in compliance with current regulations.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.