

Muriatic Acid 50 Ltrs (RXSOL-22-2205-050)

MATERIAL SAFETY DATA SHEET • SALALAH CHEMICAL, OMAN

1. Product and Company Identification

www.rxmarine.com

Product Name	RXSOL-22-2205-050
Product Type	Muriatic Acid

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333 / 5555 / 9999
Fax	+91 22 2781 1318 ::AOH :0091 9821214367
Email	mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Ingredient	CAS No	Percent
HYDROGEN CHLORIDE	7647-01-0	9 - 36
Water	7732-18-5	63-91

3. Hazards Identification

www.rxmarine.com

NFPA RATINGS (SCALE 0-4)	
	HEALTH = 3
	FIRE = 0
	REACTIVITY = 0
HMIS RATINGS (SCALE 0-4)	
	HEALTH = 3
	FLAMMABILITY = 0
	REACTIVITY = 0

EMERGENCY OVERVIEW	
COLOR	colorless
PHYSICAL FORM	liquid
ODOR	pungent odor

SIGNAL WORD	DANGER
MAJOR HEALTH HAZARDS	CAUSES BURNS TO THE RESPIRATORY TRACT, SKIN, EYES AND
GASTROINTESTINAL TRACT	CAUSES PERMANENT EYE DAMAGE. MAY BE HARMFUL OR FATAL IF SWALLOWED.
PHYSICAL HAZARDS	May spatter or generate heat when mixed with water. Contact with metals may evolve flammable hydrogen gas.
PRECAUTIONARY STATEMENTS	Do not breathe vapor or mist. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling. Use only with adequate ventilation.

SHORT TERM EXPOSURE	burns, eye damage, blindness
LONG TERM EXPOSURE	to our knowledge, no effects are known
INGESTION	
SHORT TERM EXPOSURE	Burns
LONG TERM EXPOSURE	ingestion of harmful amounts is unlikely
CARCINOGEN STATUS	
OSHA	no
NTP	no
IARC	no

4. First Aid Measures

www.rxmarine.com

Inhalation	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. If respiration or pulse has stopped, have a trained person administer Basic Life Support (Cardio-Pulmonary Resuscitation/Automatic External Defibrillator) and CALL FOR EMERGENCY SERVICES IMMEDIATELY.
Skin Contact	Immediately flush contaminated areas with water. Remove contaminated clothing, jewelry, and shoes immediately. Wash contaminated areas with soap and water. Thoroughly clean and dry contaminated clothing and shoes before reuse. Discard footwear which cannot be decontaminated. GET MEDICAL ATTENTION IMMEDIATELY.
EYE CONTACT	Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissues. Washing eyes within several seconds is essential to achieve maximum effectiveness. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION	Never give anything by mouth to an unconscious or convulsive person. If swallowed, do not induce vomiting. Give large amounts of water. If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. GET MEDICAL ATTENTION IMMEDIATELY.
NOTE TO PHYSICIAN	The absence of visible signs or symptoms of burns does NOT reliably exclude the presence of actual tissue damage. Probable mucosal damage may contraindicate the use of gastric lavage.

5. Fire-fighting Measures

www.rxmarine.com

FIRE AND EXPLOSION HAZARDS	May release toxic gases.
EXTINGUISHING MEDIA	Use extinguishing agents appropriate for surrounding fire.
FIRE FIGHTING	Keep unnecessary people away, isolate hazard area and deny entry. Wear NIOSH approved positive-pressure self-contained breathing apparatus. Move containers from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Cool containers with water.
SENSITIVITY TO MECHANICAL IMPACT	Not sensitive
FLASH POINT	not flammable
HAZARDOUS COMBUSTION PRODUCTS	Thermal decomposition products or combustion: hydrogen chloride

6. Accidental Release Measures

www.rxmarine.com

OCCUPATIONAL RELEASE: Evacuation of surrounding area may be necessary for large spills. Wear appropriate personal protective equipment recommended in Section 8 of the MSDS. Completely contain spilled material with dikes, sandbags, etc. Shut off ventilation system if needed. Reprocess or reuse if possible. Neutralize with soda ash or dilute caustic soda. Collect with appropriate absorbent and place into suitable container. Liquid material may be removed with a vacuum truck. Keep out of water supplies and sewers. This material is acidic and may lower the pH of the surface waters with low buffering capacity. Releases should be reported, if required, to appropriate agencies. Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800) 424-8802 (USA) or (202) 426-2675 (USA).

7. Handling and Storage

www.rxmarine.com

STORAGE	Store and handle in accordance with all current regulations and standards. Store in rubber-lined steel, acid-resistant plastic or glass containers. Keep containers tightly closed and properly labeled. Store in a cool, dry place. Store in a well-ventilated area. Do not store in aluminum container or use aluminum fittings or transfer lines. Dike and vent storage tanks. Keep separated from incompatible substances (see Section 10 of the MSDS).
HANDLING	Avoid breathing vapor or mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. When mixing, slowly add to water to minimize heat generation and spattering.

8. Exposure controls and personal protection

www.rxmarine.com

EXPOSURE LIMITS	HYDROGEN CHLORIDE, ANHYDROUS:
HYDROGEN CHLORIDE (HYDROCHLORIC ACID)	5 ppm (7 mg/m ³) OSHA ceiling, 2 ppm ACGIH ceiling
VENTILATION	Use closed systems when possible. Provide local exhaust ventilation where vapor or mist may be generated. Ensure compliance with applicable exposure limits.
EYE PROTECTION	Wear safety glasses with side shields. Wear chemical safety goggles with a faceshield or chemical splash hood. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.
CLOTHING	Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Always place plants legs over boots.
GLOVES	Wear appropriate chemical resistant gloves.
PROTECTIVE MATERIAL TYPES	neoprene, nitrile, polyvinyl chloride (PVC), rubber, Kappler ® CPF3, Tychem
IMMEDIATELY DANGEROUS TO LIFE OR HEALTH	50 ppm
RESPIRATOR	Where vapor concentration exceeds or is likely to exceed applicable exposure limits, a NIOSH approved respirator with acid gas canister is required. When an air-purifying respirator is not adequate for spills and/or emergencies of unknown concentrations, a NIOSH approved self-contained breathing apparatus or airline respirator with full-face piece is required. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

9. Physical and chemical properties

www.rxmarine.com

PHYSICAL STATE	liquid
Appearance	Clear.
COLOR	colorless
Odor	pungent odor
MOLECULAR WEIGHT	36.46
MOLECULAR FORMULA	HCl
BOILING POINT	140-221F (60.0 – 105 C)
FREEZING POINT	-29 to 5 F (-34 to -15 C)
VAPOR PRESSURE	14.6 – 80 mmHg @ 20 C
VAPOR DENSITY (air = 1)	1.3 @ 20 C

SPECIFIC GRAVITY (water = 1)	1.05 - 1.18
BULK DENSITY	8.75 - 9.83 lbs/gal
WATER SOLUBILITY	100%
PH	2 (0.2% solution)
VOLATILITY	9 - 36% by volume
ODOR THRESHOLD	0.3 ppm (causes olfactory fatigue)
EVAPORATION RATE	1.00 (butyl acetate = 1)
COEFFICIENT OF WATER/OIL DISTRIBUTION	n/a

10. Stability and reactivity

www.rxmarine.com

REACTIVITY	Stable at normal temperatures and pressure.
CONDITIONS TO AVOID	Avoid heat, flames, sparks and other sources of ignition. Contact with water may produce a strong exothermic reaction with spattering. Contact with metals may evolve flammable hydrogen gas. Hydrogen chloride may react with cyanide, forming lethal concentrations of hydrocyanic acid.
INCOMPATIBILITIES	metals, alkalis (such as sodium hydroxide), mercuric sulfate, perchloric acid, carbides of calcium, cesium, rubidium, acetylides of cesium and rubidium, phosphides of calcium and uranium, lithium silicide.
HAZARDOUS DECOMPOSITION	Thermal decomposition products or combustion: hydrogen chloride
POLYMERIZATION	will not polymerize

11. Toxicological information

www.rxmarine.com

MURIATIC ACID (ALL GRADES)	
----------------------------	--

TOXICITY DATA	Hydrochloric Acid: 900 mg/kg oral-rabbit LD50; 1108 ppm/1 hour(s) inhalation-rat; 3124 ppm/1 hour(s) inhalation-rat LC50. Rinsed Draize Test: 5 mg/30 second(s) rabbit-eye mild. Standard Draize Test: 4% / 24 hour(s) skin-human mild. Inhalation will cause severe irritation and possible burns with coughing and choking. If inhaled deeply, edema and hemorrhage of the lungs may occur. Levels of 10-35 ppm may cause irritation of throat and 50-100 ppm is unbearable for 1 hour. Inflammation, destruction of nasal passages and breathing difficulties may occur with higher concentration and/or erosion of teeth. Contact with eyes causes immediate severe irritation with possible burns, permanent visual impairment, or total loss of sight. Contact with fumes or liquid may produce corrosive burns. Dermal exposure also results in irritation, pain, dermatitis, and ulceration. Ingestion may cause immediate burns of the mouth, esophagus, and stomach. Ingestion may cause intense pain, nausea, vomiting, bleeding, circulating collapse, shock and death.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	RE: respiratory system (including asthma and other breathing disorders)

12. Ecological information

www.rxmarine.com

ECOTOXICITY DATA	
FISH TOXICITY	Hydrochloric Acid: 178 mg/L LC50 Goldfish (1 to 2 hour survival time); 100-300 mg/L LC50 Shrimp. 3.6 mg/L 48 hour(s) (static) LC50 Bluegill. This material is believed to be toxic to aquatic life.
FATE AND TRANSPORT	
BIODEGRADATION	This material is inorganic and not subject to biodegradation.
PERSISTENCE	This material is believed not to persist in the environment. This material is believed to exist in the disassociated state in the environment. SOIL: Hydrogen chloride will sink into the soil. The acid will dissolve some soil material (in particular, anything with a carbonate base) and will be somewhat neutralized. The remaining portion is thought to transport downward to the water table. WATER: Dissociates almost completely and will be neutralized by natural alkalinity and carbon dioxide.
BIOCONCENTRATION	This material is believed not to bioaccumulate.

13. Disposal considerations

www.rxmarine.com

Reuse or reprocess if possible. Dispose in accordance with all applicable regulations.

Subject to disposal regulations	regulations: U.S. EPA 40 CFR 262.
Hazardous Waste Number(s)	D002.

14. Transport information

www.rxmarine.com

U.S. DOT 49 CFR 172.101	
PROPER SHIPPING NAME	Hydrochloric acid solution
ID NUMBER	UN1789
HAZARD CLASS OR DIVISION	8
PACKING GROUP	II
LABELING REQUIREMENTS	8
DOT HAZARDOUS SUBSTANCE(S)	Hydrochloric acid 5000 lb(s) (2270 kg(s))
CANADIAN TRANSPORTATION OF DANGEROUS GOODS	
SHIPPING NAME	Hydrochloric acid solution
UN NUMBER	UN1789
CLASS	8
PACKING GROUP/RISK GROUP	II

15. Regulatory information

www.rxmarine.com

U.S. REGULATIONS	
CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4)	
HYDROGEN CHLORIDE	5000 LBS RQ (liquid)
CHLORINE	10 LBS RQ
SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30)	
HYDROGEN CHLORIDE	500 LBS TPQ (gas)
SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21)	
ACUTE	yes
CHRONIC	no
FIRE	no
REACTIVE	no
SUDDEN RELEASE	no
SARA TITLE III SECTION 313 (40 CFR 372.65)	
HYDROGEN CHLORIDE	aerosol form only

This product contains a toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372. Refer to Section 3.

OSHA PROCESS SAFETY (29 CFR 1910.119)	HYDROGEN CHLORIDE: 5000 LBS TO (gas)
CHLORINE	1500 LBS TQ
FDA	This material has Generally Recognized as Safe (GRAS) status under specific FDA regulations. Additional information is available from the Code of Federal Regulations (CFR) which is accessible on the FDA's website.
STATE REGULATIONS	

California Proposition 65	This product may contain contaminants known to the State of California to cause cancer or reproductive toxicity as listed under Proposition 65 State Drinking Water and Toxic Enforcement Act.
NEW JERSEY WORKER AND COMMUNITY RIGHT TO KNOW	
REPORTING REQUIREMENT	
WATER	7732-18-5 63 - 91%
HYDROGEN CHLORIDE 7647-01-0	936%
RIGHT TO KNOW HAZARDOUS SUBSTANCE LIST	HYDROGEN CHLORIDE 7647-01-0 9-36% CHLORINE 7782-50-5 0 - 50 ppm
SPECIAL HEALTH HAZARD SUBSTANCE LIST	HYDROGEN CHLORIDE 7647-01-0 9-36%
PENNSYLVANIA RIGHT TO KNOW	
REPORTING REQUIREMENT	WATER 7732-18-5 63 - 91% HYDROGEN CHLORIDE 7647-01-0 0 36%
HAZARDOUS SUBSTANCE LIST	HYDROGEN CHLORIDE 7647-01-0 9-36%
ENVIRONMENTAL HAZARDOUS SUBSTANCE LIST	HYDROGEN CHLORIDE 7647-01-0 9-36%
SPECIAL HAZARDOUS SUBSTANCE LIST	not regulated
CANADIAN REGULATIONS	WHMIS CLASSIFICATION: E
NATIONAL INVENTORY STATUS	
U.S. INVENTORY (TSCA)	All the components of this substance are listed on or are exempt from the inventory.
TSCA 12(b) EXPORT NOTIFICATION	not listed
CANADA INVENTORY (DSL/NDL)	All components of this product are listed on the DSL.

16. Other information

www.rxmarine.com

IMPORTANT: The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GAURANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SUITABILITY, STABILITY OR OTHERWISE. The information included herein is not intended to be all-inclusive as to the appropriate manner and/or conditions of use, handling and/or storage. Factors pertaining to certain conditions of storage, handling, or use of this product may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding

safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended to, and nothing herein shall be construed as a recommendation to, infringe any existing patents or violate any laws, rules, regulations or ordinances of any governmental entity.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.