

Lithium Bromide 45 (RXSOL-39-9001-300)

MATERIAL SAFETY DATA SHEET • SALALAH CHEMICAL, OMAN

1. Product and Company Identification

www.rxmarine.com

Product Name	Lithium Bromide 45
Part Number	RXSOL-39-9001-300
Chemical Formula	LiBr
Chemical Family	Inorganic Bromide
CAS No	7550-35-8
Molecular Weight	86.85
Type of product and use	Inorganic solution used as desiccate medium in air conditioning and cooling systems.

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Chennai, Visakhapatnam, Kolkata, Fujairah, Muscat OMAN

Phone	+91 22 27815540 / 41 / 42
Fax	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	123@rxmarine.com
Website	www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Name of Substance	Cas Number	EC Number	Wight %
Lithium Bromide	7550-35-8	231-439-8	45

3. Hazards Identification

www.rxmarine.com

Signal Word	Warning
Adverse human health effects	Risk of serious damage to eyes.

4. First Aid Measures

www.rxmarine.com

Eye Contact:	Holding the eyelids apart flush eyes promptly with copious flowing water for at least 20 minutes. Get medical attention immediately.
Skin Contact :	Remove contaminated clothing. Wash skin thoroughly with mild soap and plenty of water for at least 15 minutes. Wash clothing before reuse. Get medical attention if irritation persists.

Inhalation:	In case of inhalation or breathing fumes released from heated material, remove person to fresh air. Keep him quiet and warm. Apply artificial respiration if necessary and get medical attention immediately.
Ingestion:	If swallowed, wash mouth thoroughly with plenty of water and give water or milk to drink. Get medical attention immediately. NEVER GIVE AN UNCONSCIOUS PERSON ANYTHING TO DRINK.

5. Fire-fighting Measures

www.rxmarine.com

Flash Point	None.
Auto-ignition temperature	Not Available.
Flammable/Explosion limits	Not Available
Etinguishing media	Material is not combustible. Use extinguishing media appropriate to surrounding fire conditions.
Fire fighting procedure	Cool containers with water spray. In closed stores, provide fire-fighters with self-contained breathing apparatus in positive pressure mode.
Usual fire and explosion hazards	None known.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions	Wear respirator, chemical safety goggles, rubber gloves and boots.
After spillage / leakage	Absorb on sand or vermiculite and place in closed container for disposal. Ventilate area and wash spill site after material pick-up is complete. Avoid access to streams, lakes or ponds.
Disposal Considerations	Avoid access to streams, lakes or ponds. Observe all federal, state and local environmental regulations when disposing of this material.

7. Handling and Storage

www.rxmarine.com

Handling	Avoid bodily contact. Keep containers tightly closed.
Storage	Store in a cool, well-ventilated area away from incompatible materials.

8. Exposure controls and personal protection

www.rxmarine.com

Ventilation requirements	Provide adequate ventilation. Use local exhaust as necessary, especially under misting conditions.
Personal protection equipment	
Respiratory protection :	Approved respirator.
Gloves :	Rubber gloves.

Eye Protection:	Chemical safety goggles.
Others :	Body covering clothes and boots.
Industrial hygiene :	Safety shower and eye bath should be provided.Do not eat, drink or smoke until after work showering and changing clothes.

9. Physical and chemical properties

www.rxmarine.com

Appearance:	Clear, colourless to yellow liquid, odourless.
Melting Point / range :	10oC (58%)
Boiling Point / range :	145 - 147oC (55%)
Vapour Pressure :	2.1 mm Hg at 20oC (55%)
Relative vapour density (air=1) :	Not available.
Evaporation rate (either=1) :	Not available.
Solubility in Water :	70 gr/100ml at 101oC
Solubility in other Solvent:	Miscible with Methanol, Ethanol (absolute),n-Propanol.
Thermal decomposition :	Not available.

10. Stability and reactivity

www.rxmarine.com

Stability	Stable under normal conditions.
Materials to avoid :	Strong acids.
Conditions to avoid :	None known.
Hazardous decomposition-products :	Hydrobromic Acid gas above 200oC
Hazardous Polymerization:	Will not occur.

11. Toxicological information

www.rxmarine.com

Effect of overexposure	
Ocular :	Severe irritant.
Dermal :	Mild irritant to intact skin.
Inhalation :	May irritate the upper respiratory tract.
Ingestion :	May cause vomiting, nausea, diarrhea and ataxia. Slurred speech, blurred vision, dizziness, sensory loss, convulsions and stupor may occur in cases of large intake.
Chronic toxicity :	Repeated skin contact may cause dermatitis.Repeated oral intake of bromides may affect the central nervous system. Warning symptoms include mental dullness, slurred speech,weakened memory, apathy, anorexia, constipation, drowsiness and loss of sensitivity to touch and pain.
Carcinogenicity :	Not known to be a carcinogen.
Mutagenicity :	Not mutagenic by the Ames Test.

12. Ecological information

www.rxmarine.com

Aquatictoxicity	: 48 Hour-EC50
Daphnia magna	: 45 mg/l

13. Disposal considerations

www.rxmarine.com

Waste treatment Method	Avoid access to streams, leaks or ponds. Observe all federal, state and local environmental regulations when disposing of this material.
------------------------	--

14. Transport information

www.rxmarine.com

UN No. :	Not regulated.
IMO-IMDG CODE :	Not regulated.
ICAO / IATA :	Not regulated.
RID / ADR :	Not regulated.
US DOT :	Not regulated.

15. Regulatory information

www.rxmarine.com

Classification :	Irritant symbol required and dangerous to the environment.
R Phrase(s) :	R 41 : Risk of serious damage to eyes. R 52 : Harmful to aquatic organisms.
S Phrases :	S 26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S 39 : Wear eye / face protection. S 61 : Avoid release to the environment. Refer to special instructions / Safety Data Sheets.

16. Other information

www.rxmarine.com

Revision Information:	None
-----------------------	------

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if RX Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
-------------------	---