

WhiteSpirit Less 20 Percent AROMATICS (RXSOL-19-1484-025)

MATERIAL SAFETY DATA SHEET • SALALAH CHEMICAL, OMAN

1. Product and Company Identification

www.rxmarine.com

Product Name	RXSOL-19-1484-025
Product Type	Whitespirit (Sol 20%AROMATICS)

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333 / 5555 / 9999 / 27611360
Fax	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	mail@rxmarine.com
Website	www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemica Name	CAS #	PROPORTION
Medium aliphatic petroleum solvent	64742-88-7	>60%
Light aromatic petroleum solvent	6742-95-6	10 - 30%

3. Hazards Identification

www.rxmarine.com

Swallowed	May cause symptoms of stomach pain, nausea and vomiting. Ingestion of large does may cause unconsciousness. If vomiting occurs after ingestion, small droplets of the liquid may enter the lungs (aspiration) with the risk of chemical pneumonia being induced.
Eye	Liquid may cause moderate to sever eye irritation, vapour is irritating.
Skin	Contact with the product may cause defatting and contribute to dermatitis.
Inhaled	Inhalation may cause headache, nausea and dizziness. Higher concentrations may cause unconsciousness and coma. Death may result from severe and continued over-exposure.
Chronic Effects	Inhalation and ingestion are the routes of entry into the body. The product defats the skin and prolonged or repeated contact may contribute to dermatitis.
Risk Phrase	R65 - Harmful: May cause lung damage if swallowed.

4. First Aid Measures

www.rxmarine.com

Skin	Remove contaminated clothing and wash thoroughly with soap and water. Use water alone, if soap is unavailable. Apply a moisturising hand cream, if available. Seek medical attention if any soreness or inflammation of the skin persists or develops later. Launder affected clothing before re-use.
Inhalation	Remove to fresh air. Keep warm and at rest. If breathing is laboured, hold in a half upright position (this assists respiration). Apply artificial respiration if breathing has stopped. Seek URGENT medical attention for all but the most minor cases of over exposure.

Safety	S2 - Keep out of reach of children
Phrase	S23 -Do not breathe vapour
	S24 -Avoid contact with skin
	S62 -If swallowed, do not induce vomiting: seek medical advice immediately and show container or label to medical staff.

5. Fire-fighting Measures

www.rxmarine.com

FLAMMABLE	Solvent vapours can form explosive mixtures with air in poorly ventilated conditions. Containers may explode if heated. Vapour is heavier than air and may travel along the ground, distant ignition is possible. Wear self contained breathing apparatus. If possible remove containers from the vicinity of the fire. Otherwise keep containers as cool as possible by spraying with water, from a protected position.
Extinguishing Media	Foam, powder (bicarbonate or ammonium phosphate based) or carbon dioxide. Water is not effective for fire fighting and direct contact with water should be avoided.

6. Accidental Release Measures

www.rxmarine.com

Care for environmental protection

Do not allow product to enter drains or waterways where ground or surface water may be affected.

7. Handling and Storage

www.rxmarine.com

Storage / Transport: Class 3 Flammable Liquids should not be transported or stored with goods of:

Class 1 (Explosives)

Class 2.1 (Flammable gases, where both flammable liquid and flammable gases are in bulk)

Class 2.3 (Poisonous gases)

Class 4.2 (Spontaneously combustible substances)

Class 5.1 (Oxidising agents)

Class 6 (Poisonous (toxic) substances, where the flammable liquid is nitromethane)

Class 7 (Radioactive substances)

Store in a flammable liquids area, designated no smoking, away from all sources of ignition, out of direct sunlight in a cool well ventilated area below 25°C. Higher temperatures may cause pressure build up inside containers. Protect containers against physical damage. Ventilation along the floor is advised

8. Exposure controls and personal protection

www.rxmarine.com

Personal Protection	Safety goggles, overalls and PVC gloves. A respirator with organic vapour filter will be required unless the work area is well ventilated. In confined or poorly ventilated areas use air supplied breathing apparatus. NB: TAKE THE LIMITS OF ABSORPTION CAPACITY INTO ACCOUNT. CHANGE FILTERS REGULARLY.
Flammability	FLAMMABLE. Solvent vapours can form flammable mixtures with air. May evolve toxic fumes if heated or burned. The product may react with strong oxidising agents such as liquid or powdered chlorine. Not smoking

9. Physical and chemical properties

www.rxmarine.com

Appearance / Odour	Water white liquid with a slight kerosene odour
Boiling Point	147°C - 196°C

Vapour Pressure	6mmHg
Specific Gravity	0.79
Flash Point	370C
Explosive Limit (%)	L.E.L. 0.9% U.E.L. 7.0%
Solubility in Water	Negligible (0.1%mass)
Other Properties	pH: Not Applicable

10. Stability and reactivity

www.rxmarine.com

Condition to Avoid	Heat, Flame & Other Sources of Ignition.
Materials to Avoid	Do not subject to Reducing /Oxidizing Agents.
Hazardous Decomposition Products	Do not occur

NOTE : No decomposition if used according to specifications.

11. Toxicological information

www.rxmarine.com

Skin Irritation	irritant wash with soap water
Eye Irritat	Moderate irritant , flush with copious amounts of water
Sensitization	Not Sensitizing .

12. Ecological information

www.rxmarine.com

Comment Not applicable

Ecotoxicity Not applicable , Readily biodegradable

Water hazard class 2 (self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

13. Disposal considerations

www.rxmarine.com

This material must be disposed with local national regulations.

Product Recommendation

Must be not dispose of together with household garbas.

Can be burnt under adherence to the necessary technical regulations.

Disposal must be made according to official regulations.

Can be reused or recycled after cleaning .

14. Transport information

www.rxmarine.com

LAND TRANSPORT

9, Miscellionus Dangrous, substance and article

15. Regulatory information

www.rxmarine.com

- Hazard designation of product: Xi Irritant.

- Irritating to eyes and skin.

- Safety phrases

2 - Keep out reach of children If swallowed, seek medical attention immediately

22 - Harmful if swallowed

26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.

23 - Do not Breathe

27 - After contact with skin, wash immediately with plenty of water and soap and rinse thoroughly.

41 - Risk of serious damage to eyes

- National regulations

16. Other information

www.rxmarine.com

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing data specification sheet Environment protection department.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.